



1316 Commerce Street, Birmingham, AL 35127  
Office: (205) 545 - 8601 Facsimile (205) 841 - 3242  
[www.protectivecagesllc.com](http://www.protectivecagesllc.com)

## **HVAC CONDENSER GUARD 2500 SERIES**

**OB2500:** This is one of our most secure cage designs. It is an open back cage engineered for the rear of the cage to be placed close to a building or structure. The unit is comprised four panels with a 1" x 1/8" mild steel angle outer frame, and 16 gauge 1/2" expanded metal. The unit incorporates a hinge on the bottom of the front panel allowing the cage to tilt out of the way for total access to the HVAC condenser. The rear legs are secured with padlocks, supplied by customer, minimizing unauthorized access. Exterior grade fasteners located inside the cage securely hold the panels together. The unit can be installed on concrete or soil. The standard finish process is grinding of exterior welds, application of a powder coat primer, and finally a black powder coat is baked onto the cage. Additional colors are available upon request.

**Cage Sizes:** Each cage is sized specific to the end application.

**Finishes:** Optional colors and trim are available. We can supply you a color pallet and work with you on a desired appearance

**Pricing:** Visit [www.protectivecagesllc.com](http://www.protectivecagesllc.com) to complete a quotation request form or simply call us.

**CB2500:** Our most secure cage. It is a closed back cage engineered to completely enclose the HVAC condenser unit. The unit is comprised of five panels with a 1" x 1/8" mild steel angle outer frame, and 16 gauge 1/2" expanded metal. A fifth panel made of the same materials constitutes the hinged rear door. Additional support bars made of 16 gauge angle are placed in the center of the panels. The inner support bars are spaced no farther apart than 24" on center. The unit incorporates two hinges on the bottom of the front panel and top of the rear door allowing the cage to tilt out of the way for total access to

the HVAC condenser. The rear legs are secured with padlocks, supplied by customer, minimizing unauthorized access. Exterior grade fasteners located inside the cage securely hold the panels together. The unit can be installed on concrete or soil. The standard finish process is grinding of exterior welds, application of a powder coat primer, and finally a black powder coat is baked onto the cage. Additional colors are available upon request.

**Cage Sizes:** Each cage is sized specific to the end application.

**Finishes:** Optional colors and trim are available. We can supply you a color pallet and work with you on a desired appearance

**Pricing:** Each cage order is priced depending on the size and complexity of the product. Visit our web site at [www.protectivecagesllc.com](http://www.protectivecagesllc.com), to complete a quotation request form or simply CALL US.